

COLONIAL WOOD OIL — SAFETY DATA

Revision Date: 12 May 2026 **Product Code:** PF-0211-P **Manufacturer:** TAG Rifleworks, LLC
Product Type: Proprietary Polymerizing Wood-Finish Oil System

1. Identification

- **Product Name:** Colonial Wood Oil
- **Product Description:** Proprietary polymerizing oil system for wood finishing and protection
- **Recommended Use:** Hand-applied finish for cured hardwood surfaces
- **Restrictions:** Not for ingestion; not for uncured food-contact surfaces
- **Emergency Contact:** TAG Rifleworks, LLC 9562447472
- Poison Control Center (U.S.): **1-800-222-1222**

2. Hazard Identification

GHS Classification:

- Flammable Liquid — Category 3
- Skin Irritation — Category 2
- Aspiration Hazard — Category 1
- STOT-SE — Category 3 (respiratory)

Signal Word: DANGER

Hazard Statements:

- Flammable liquid and vapor
- May be fatal if swallowed and enters airways
- Causes skin irritation
- May cause drowsiness or dizziness
- Spontaneous combustion hazard: oil-soaked rags may self-ignite

Precautionary Statements:

- Keep away from heat, sparks, and open flame
- Use only with adequate ventilation
- Wear nitrile gloves and eye protection
- Store in tightly closed container in cool, dry location

3. Composition / Information on Ingredients

This product contains a proprietary blend of polymerizing oils, resin-modified oil systems, and low-aromatic solvent carriers. All components protected under Trade Secret Claim 29-PF-A.

Proprietary Component	Disclosure Status
Proprietary Polymerizing Oil Blend	Trade Secret
Proprietary Resin-Modified Oil System	Trade Secret
Proprietary Low-Aromatic Solvent Carrier	Trade Secret

Exact composition withheld as a trade secret.

4. First-Aid Measures

- **Inhalation:** Move to fresh air; monitor for respiratory irritation
- **Skin Contact:** Wash thoroughly with soap and water
- **Eye Contact:** Rinse cautiously with water for several minutes
- **Ingestion:** Do **not** induce vomiting; seek immediate medical attention due to aspiration hazard

5. Fire-Fighting Measures

- **Extinguishing Media:** Dry chemical, foam, CO₂
- **Hazards:** Vapors may ignite; containers may rupture under heat
- **Special Notes:** Oil-soaked rags may self-heat and combust

6. Accidental Release Measures

- Remove ignition sources
- Absorb with inert material
- Collect in sealed waste container
- Prevent release to drains or soil

7. Handling & Storage

- Keep container sealed when not in use
- Ground/bond containers during transfer
- Store below 120°F
- Dispose of oil-soaked rags in water-filled metal container with lid

8. Exposure Controls / PPE

- **Ventilation:** Mechanical or natural ventilation recommended

- **Respiratory:** Organic vapor protection if ventilation inadequate
- **Skin:** Nitrile gloves
- **Eyes:** Safety glasses or splash goggles

9. Physical & Chemical Properties

- Appearance: Amber, medium-viscosity liquid
- Odor: Mild, low-aromatic
- Flash Point: >100°F (proprietary estimate)
- VOC Content: Proprietary
- Solubility: Not water-soluble

10. Stability & Reactivity

- Stable under normal conditions
- Avoid heat, sparks, oxidizers
- Decomposition may produce carbon oxides and aldehydes

11. Toxicological Information

- Prolonged skin exposure may cause irritation
- High vapor concentrations may cause CNS effects
- Aspiration hazard if swallowed

12. Ecological Information

- Harmful to aquatic life with long-lasting effects
- Avoid release to environment

13. Disposal Considerations

- Dispose of in accordance with local regulations
- **Oil-soaked rags must be submerged in water and sealed before disposal**

14. Transport Information

- UN1263 — Paint Related Material
- Class 3 Flammable Liquid
- Packing Group III

15. Regulatory Information

- All components compliant under trade-secret exemption
- SARA 311/312: Fire hazard, acute health hazard

16. Other Information

Prepared by: TAG Rifleworks, LLC Proprietary SDS — Distribution restricted Revision: 1.0-P